

SAFETY DATA SHEET (SDS)

SDS Date: 05/29/2015 Rev. 3 Date: 11-13-2020

SECTION 1: Identification of the substance/mixture and of the company

PRODUCT NAME: AQUAGARD WATERBASE BOTTOM PAINT

PRODUCT CODES 110001, 10002, 10003, 10004, 10005, 10006, 10007, 10101, 10102, 10103, 10104, 10105, 10106, 10107, 10201, 10202, 10203, 10204, 10205, 10206, 10207

USES: Bottom paint for pleasure crafts.

Do not use for any application other than its intended use. This Safety Data Sheet has been updated in accordance with the Global Harmonized System (GHS).

MANUFACTURER: New Nautical Coatings, Inc.

ADDRESS:

14805 49th St. North, Clearwater, FL 33762

Tel:

888-353-9335

CHEMTREC 24 Hour Emergency Response:

1-800-424-9300

PREPARED BY: Flexabar Information Services

SECTION 2: HAZARD(S) IDENTIFICATION

EMERGENCY OVERVIEW: Causes irritation to the skin, eyes, mucous membranes and respiratory tract. Can be absorbed through the skin causing systemic effects.

GHS Classification:

H302 Harmful if swallowed

H313 May be Harmful in contact with skin

H373 May cause damage to organs through prolonged or repeated exposure

H410 Very toxic to aquatic life with long lasting effects

GHS Label elements:

Pictograms:



Signal Word:

Danger

Hazard Statements:

Description

H302 Harmful if swallowed

H313 May be harmful in contact with Skin

H373 May cause damage to organs through prolonged or repeated exposure

H410 Very toxic to aquatic life with long lasting effects

Precautionary Statements: **Description**

P262 Do not get in eyes, on skin or on clothing

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment

P280 Wear protective gloves/eye protection/face protection

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes.

Remove contact lenses if present and easy to do-continue rinsing

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P330 Rinse mouth

P331 DO NOT induce vomiting

P333+313 If skin irritation or a rash occurs: Get medical advice/attention

SAFETY DATA SHEET (SDS)

SDS Date: 05/29/2015 Rev. 2 Date: 3-27-2020

P337 If eye irritation persists
 P362 Take off contaminated clothing and wash before reuse
 P391 Control spillage
 P403+233 Store in a well ventilated place. Keep container tightly closed
 P501 Dispose of contents/container in accordance with local/national regulations

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Acrylic Copolymer Proprietary	11.0 – 19.0	Not Classified as Hazardous	
Ethylene Glycol CAS# 107-21-1	1.0 – 3.0	Acute toxicity, Oral Skin irritation Specific target organ systemic toxicity – single exposure, Oral, Central nervous system, Kidney Specific target organ systemic toxicity – repeated exposure, Oral, Central nervous system, Kidney Category 4 Category 2 Category 1 Category 2	1, 2
Dibutyl Phthalate CAS# 84-74-2	1.0 – 3.0	Reproductive toxicity Acute aquatic toxicity (Category 1B), H360 (Category 1), H440	1, 2
Zinc Oxide CAS# 1314-13-2	1.0 – 3.0	Aquatic Acute Aquatic Chronic Very toxic to aquatic life, H400 Very toxic to aquatic life with long lasting effects, H410	
Cuprous Oxide CAS# 1317-39-1	26.0 – 29.0	Acute toxicity Aquatic Acute Aquatic Chronic (4) Harmful if swallowed, H302 Very toxic to aquatic life, H400 Very toxic to aquatic life with long lasting effects, H410	1, 2

GHS Classification Scale (1 = severe; 4 = slight)

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit

[3] PBT substance or vPvb substance

SAFETY DATA SHEET (SDS)

SDS Date: 05/29/2015 Rev. 2 Date: 3-27-2020

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Important symptoms and effects, acute and delayed

Overview	Misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing Dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May be harmful if absorbed through skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data. Risk of cancer dependent on duration and level of exposure.

SECTION 5: FIRE-FIGHTING MEASURES

Conditions of flammability	Material may burn but does not ignite readily. Fire may produce irritating and or toxic gasses. Heated containers may explode.
Extinguishing media	Use dry chemical powder, CO2 or foam, water spray may be used for large fires.
Special protective equip.	Wear a self-contained breathing apparatus MSHA/NIOSH (approved or equivalent), and full protective gear.
Hazardous combustion products	Carbon oxides
Special information	Use water spray to disperse vapors and to protect personnel attempting to stop leak. Can react vigorously with oxidizing materials. Do not allow fire water contaminated with this product to enter any waterway or storm drain.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions	Wear adequate/appropriate personal protection equipment. Ventilate area if confined space.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not let product enter drains or soil. Discharge into the environment must be avoided.
Methods of containment/cleanup	Contain liquid with dirt, sand, vermiculite or other noncombustible solids. Transfer to a metal container for disposal.

SAFETY DATA SHEET (SDS)

SDS Date: 05/29/2015 Rev. 2 Date: 3-27-2020

SECTION 7: HANDLING AND STORAGE

Handling	Wear adequate personal protective equipment. Keep containers tightly closed. Avoid contact with skin or eyes.
Storage	Store in a cool, dry, well-ventilated area, protect from freezing.
Incompatibilities	Oxidizing agents, including nitric acid and peroxides.
Suitable Packing Materials	Polyethylene, poly propylene or Stainless steel (tanks/containers) Do NOT store in lead, steel or aluminum containers.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS No.	Ingredient	Source	Value
Proprietary	Acrylic Copolymer Emulsion	Supplier	No Controls
CAS# 107-21-1	Ethylene Glycol	ACGIH	100mg/m3 (CEILING) aerosol only
CAS# 84-74-2	Dibutyl Phthalate	OSHA	TWA 5mg/m3 (Table Z-1 Limits for Air Contaminants)
		ACGIH	5 mg/m3 Upper respiratory, Eye irritation, Testicular damage
		NIOSH	TWA 5 mg/m3
CAS# 1317-39-1	Cuprous Oxide	OSHA	PEL 1mg.m3 (8hr. TWA) As mists and dusts
		ACGIH	PEL 1mg.m3 (8hr. TWA) As mists and dusts
1314-13-2	Zinc Oxide	OSHA	PEL 5mg/m3 (fume) 15mg/m3 (total dust) and 5mg/m3 (respirable dust). 8hr. TWA
		ACGIH	2mg/m3 (8hr. TWA) and 10mg/m3 (STEL) for the respirable fraction
		NIOSH	5mg/m3 (fume and dust) averaged over a 10 hr. work shift, 10mg/m3 as a short term exposure limit (for fume) and 15mg/m3 (for dust), not to be exceeded at any time.

PEL = Permissible Exposure Limits
TLV = Threshold Limit Value
EL = Excursion Limit

TWA = Time Weighted Average (8 hr.)
STEL = Short Term Exposure Limit (15 min.)
WEEL = Workplace Environmental Exposure Level

Exposure Controls:

Respiratory	Select equipment to provide protection from the ingredients listed in section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor or mist levels above the applicable limits, wear appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from the ingredients Listed in section 3 of this document. Depending on site and application method specific conditions, safety glasses, chemical goggles, and or head and face protection may be required. All equipment must be thoroughly cleaned or discarded after use.
Skin	Select equipment to provide protection from the ingredients listed in section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection May be required to prevent contact. All equipment must be thoroughly cleaned or discarded after each use.
Engineering Controls	Ensure adequate ventilation to keep exposure levels at a minimum under the specific conditions.

SAFETY DATA SHEET (SDS)

SDS Date: 05/29/2015 Rev. 2 Date: 3-27-2020

Other Work Practices Emergency eye wash stations and safety showers should be available in the immediate work area. Use good Personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove exposed/spoiled clothing and wash separately before reuse. Shower after work using plenty of soap and water.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Blue, Black, Gray, Green, Horizon Blue, Red, Shark White, Teal

ODOR: Mild latex

PHYSICAL STATE: Viscous Liquid

PH AS SUPPLIED: Not Measured

BOILING POINT:

F: Not Measured

C: Not Measured

MELTING POINT:

F: Not Measured

C: Not measured

FREEZING POINT:

F: Not measured

C: Not Measured

VAPOR PRESSURE (mmHg): Not Measured

@

F:

C:

VAPOR DENSITY (AIR = 1): Heavier than air

@

F:

C:

SPECIFIC GRAVITY (H₂O = 1):

@ 1.58 - 1.61

F: 77

C:

EVAPORATION RATE: NE MIXTURE

BASIS (=1):

SOLUBILITY IN WATER: Negligible

MIXTURE

SECTION 10: STABILITY AND REACTIVITY

Reactivity	No data available
10.2. Chemical stability	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fume generation can occur if improperly handled.
10.3. Possibility of hazardous reactions	No data available
10.4. Conditions to avoid	No data available
10.5. Incompatible materials	Strong oxidizing agents.
10.6. Hazardous decomposition products	May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Hydrogen chloride, Chlorinated compounds, Carbon Dioxide and Carbon Monoxide.

SAFETY DATA SHEET (SDS)

SDS Date: 05/29/2015 Rev. 2 Date: 3-27-2020

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION

Ingredient	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation Vapor LC 50	Eye Damage/irritation
Acrylic Copolymer Emulsion	No Data Available	No Data Available	No Data Available	No Data Available
Ethylene Glycol	7712 (rat)	3500 (mouse)	2.5 mg/l (rat) (6 hr)	Not Classified
Dibutyl Phthalate	8000 (rat)	20860 (rabbit)	4250 mg/m3 (rat)	No Data
Cuprous Oxide	No Data	Not Classified	Nat Classified	Not Classified
Zinc Oxide 1314-13-2	>5000 Rat	No sensitizing effects known	5.7 mg/l (rat) (4hr)	No sensitizing effects known

All ingredient values, literature values

<u>Item</u>	<u>Category</u>	<u>Hazard</u>
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation.
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	Not Classified	Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

SAFETY DATA SHEET (SDS)

SDS Date: 05/29/2015 Rev. 2 Date: 3-27-2020

SECTION 12: ECOLOGICAL INFORMATION

Ingredient	Toxicity to fish LC50	Toxicity to invertebrates LC50	Toxicity to algae EC50	Biodegradation	Bioaccumulation	Mobility in soil
Acrylic Copolymer Emulsion	No Data Available	No Data Available	No Data Available	No Data Available	No Data Available	No Data Available
Ethylene Glycol	Low acute toxicity to fish	Low acute toxicity to aquatic invertebrates	Low acute toxicity to algae	Rapidly degradable	Not expected to bioaccumulate.	Low potential for soil adsorption
Dibutyl Phthalate	Fathead minnow 0.85 mg/l (96.0 hr)	Daphnia Magna 3.7 mg/l (96.0 hr)	No Data	81% Readily biodegradable. (C.4C of the council regulation (EC) No 440/2008)	Fat head minnow 11 day 0.0348 mg/l Bioconcentration factor (BCF): 2,165 Does not bioaccumulate	No Data Available
Cuprous Oxide	No Data Available	No Data Available	No Data Available	No Data Available	No Data Available	No Data Available
Zinc Oxide	No Data Available	No Data Available	IC50 (72h)0.21 mg/l	No Data Available	Not expected to bioaccumulate	No Data Available

All ingredient Values, literature values

Persistence and degradability No data available
Bio accumulative potential Not Measured
Mobility in soil No data available
Results of PBT and vPvB assessment This product contains no PBT/vPvB chemicals.
Other adverse effects No data available

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Waste must be disposed of in accordance with federal, state and local environmental control regulations. This product contains components that are RCRA hazardous waste. Do not flush material to drain or storm sewer. Contract to authorized disposal service. Empty containers must be handled with care due to product residue.

SECTION 14: TRANSPORT INFORMATION

UN-number: 3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (Cuprous Oxide)

The product is classified: Environmentally Hazardous Substance

Sea (IMDG):

Class: 9
PG: III
MP: Yes
EmS: F-A, S-F

MFAG: 1

Inland Waterways: To be handled locally.

Air (ICAO/IATA):

Class: 9
PG: III

Land (DOT):

Class: 9
PG: III
Primary risk label: 9

SAFETY DATA SHEET (SDS)

SDS Date: 05/29/2015 Rev. 2 Date: 3-27-2020

SECTION 15: REGULATORY INFORMATION

EPA Registration No. 44891-23

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification Not Regulated

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
Copper

EPCRA 311/312 Chemicals and RQs (>.1%):
Copper 5000 lb final RQ
Ethylene Glycol
Dibutyl Phthalate

EPCRA 302 Extremely Hazardous (>.1%):
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):
Copper
Ethylene Glycol
Dibutyl Phthalate

Mass RTK Substances (>1%):
Titanium dioxide
Zinc oxide
Ethylene Glycol
Dibutyl Phthalate

Penn RTK Substances (>1%):
1,2-Propylene glycol
Zinc oxide
Ethylene Glycol
Dibutyl Phthalate

Penn Special Hazardous Substances (>.01%):
(No Product Ingredients Listed)

RCRA Status:
(No Product Ingredients Listed)

N.J. RTK Substances (>1%):
1,2-Propylene glycol
Zinc oxide
Ethylene Glycol
Dibutyl Phthalate

N.J. Special Hazardous Substances (>.01%):
(No Product Ingredients Listed)

N.J. Env. Hazardous Substances (>.1%):
Copper

Proposition 65 – Carcinogens (>0%):
(No Product Ingredients listed)

Proposition 65 – Female Repro Toxins (>0%):
Dibutyl Phthalate

Proposition 65 – Male Repro Toxins (>0%):
Dibutyl Phthalate

Proposition 65 – Developmental Toxins (>0%):
Dibutyl Phthalate

SAFETY DATA SHEET (SDS)

SDS Date: 05/29/2015 Rev. 2 Date: 3-27-2020

SECTION 16: OTHER INFORMATION

HMIS:

Health	1
Fire	1
Physical Hazard	0

ABBREVIATIONS:

ACGIH = American Conference of Governmental Industrial Hygienists
OSHA = Occupational Safety and Health Administration
TLV = Threshold Limit Value
TWA = Time Weighted Average
PEL = Permissible Exposure Limit
STEL = Short Term Exposure Limit
NA = Not Applicable
NE = Not Established

PREPARATION INFORMATION: HMIS Hazard Ratings Scale 0 = Minimal, 1 = Slight, 2 = Moderate, 3 = Serious, 4 = Extreme

VOC: 133 gr. per liter
1.1078 lbs. per gal.

Check with supervisor for appropriate personal protection in accordance with rating.

Reviewed 3/27/2020

DISCLAIMER:

The information contained herein is based on data provided by our suppliers and relates only to the specific material identified. Flexabar Corporation believes that the information is accurate and reliable as of the preparation date of this material safety data sheet and reflects our best judgement, but no representation, guarantee or warranty expressed or implied is made as to the accuracy, reliability or completeness of the information. Flexabar Corporation urges persons receiving this information to make their own determination as to the information's suitability and completeness for their particular application.

End of Document