

# SAFETY DATA SHEET (SDS)

SDS Date: 07/31/2015

Rev. 4 Date: 5 14 2020

---

## SECTION 1: Identification of the substance/mixture and of the company

---

**PRODUCT NAME:** AQUGARD 190 Water Based Primer  
**PRODUCT CODES** 25009, 25109

**USES:**

Primer for fiberglass, aluminium and steel hulls.  
Do not use for any application other than its intended use.

This Safety Data Sheet has been updated in accordance with the Global Harmonized System (GHS).

**MANUFACTURER:** New Nautical Coatings, Inc.

**ADDRESS:**

14805 49th St. North  
Clearwater, FL 33762

Tel: 888-353-9335

**CHEMTREC 24 Hour Emergency Response:** 1-800-424-9300

**PREPARED BY:** Flexabar Information Services

---

## SECTION 2: HAZARD(S) IDENTIFICATION

---

**EMERGENCY OVERVIEW:**

Causes irritation to the skin, eyes, mucous membranes and respiratory tract.  
Can be absorbed through the skin causing systemic effects.

**GHS Classification:**

H302 Harmful if swallowed  
H313 May be Harmful in contact with skin  
H373 May cause damage to organs through prolonged or repeated exposure

**GHS Label elements:**

**Pictograms:**



**Signal Word:**

**WARNING**

**Hazard Statements:**

**Description**

H302 Harmful if swallowed  
H313 May be harmful in contact with Skin  
H373 May cause damage to organs through prolonged or repeated exposure

**Precautionary Statements:**

**Description**

P262 Do not get in eyes, on skin or on clothing  
P270 Do not eat, drink or smoke when using this product.  
P280 Wear protective gloves/eye protection/face protection  
P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P302+352 IF ON SKIN: Wash with soap and water  
P305+351+338 IF IN EYES: Rinse continuously with water for several minutes.  
Remove contact lenses if present and easy to do-continue rinsing  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
P330 Rinse mouth  
P331 DO NOT induce vomiting  
P333+313 If skin irritation or a rash occurs: Get medical advice/attention  
P337+313 If eye irritation persists get medical advice/attention

# SAFETY DATA SHEET (SDS)

SDS Date: 07/31/2015 Rev. 4 Date: 5/14/2020

P362 Take off contaminated clothing and wash before reuse

P391 Control spillage

P403+233 Store in a well ventilated place. Keep container tightly closed

P501 Dispose of contents/container in accordance with local/national regulations

## SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Acrylic Copolymer Proprietary	11.0 – 19.0	Not Classified as Hazardous	
Ethylene Glycol CAS# 107-21-1	1.0 – 3.0	Acute toxicity, Oral Skin irritation Specific target organ systemic toxicity – single exposure, Oral, Central nervous system, Kidney Specific target organ systemic toxicity – repeated exposure, Oral, Central nervous system, Kidney Category 4 Category 2 Category 1 Category 2	1, 2
Zinc Oxide CAS# 1314-13-2	1.0 – 3.0	Aquatic Acute Very toxic to aquatic life, H400 Aquatic Chronic Very toxic to aquatic life with long lasting effects, H410	1,2
Titanium Dioxide CAS No. 13463-64-7	5.0 - 10.0	Carcinogenicity – IARC listed; Group 2B (possibly carcinogenic to humans) through inhalation not ingestion. Not listed as carcinogen by NTP, ACGIH, OSHA or the European Union.	1, 2
Carbon Black CAS No. 1333-86-4	0.5 -1.0	Acute Toxicity – No evidence of adverse effects from available data Acute Eye – High dust concentrations may cause mechanical irritation to eye. Acute Skin – May cause mechanical irritation, soiling and skin drying. Sensitization – No cases of sensitization have been reported in humans Carcinogenicity – IARC listed; Group 2B (possibly carcinogenic to humans). Not listed as carcinogen by NTP, ACGIH, OSHA or the European Union. There are no known human carcinogenic effects related to the PAH content of carbon blacks. Recent research has shown that the PAH content of carbon blacks is not released in biological fluids and thus not available for biological activity.	1, 2
Calcium Carbonate CAS No. 1317-65-3	2.0 – 4.0	Not Classified	1,2

# SAFETY DATA SHEET (SDS)

SDS Date: 07/31/2015 Rev. 4 Date: 5/14/2020

<b>Quartz (fine fraction)</b> CAS No. 14808-60*-7	.008 - .016	Carc. 1A, H350 STOT SE 3, H335 STOT SE1, H370	1,2
<b>N Methyl Pyrrolidone</b> CAS No. 8752-50-4	1.0 – 3.0	Flammable Liquid Eye irritation Reproductive toxicity Specific target organ systemic toxicity	Cat. 4 Cat.2A Cat. 1B Cat.3
<b>2-butoxiethanol</b> CAS No. 111-76-2	1.0 – 3.0	Flammable Liquid Acute toxicity (oral) Eye irritation Skin corrosion/Irritation Aspiration hazard	Cat. 4 Cat. 4 Cat.2A Cat. 2 Cat.1

GHS Classification Scale (1 = severe; 4 = slight)

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit

[3] PBT substance or vPvb substance

## SECTION 4: FIRST AID MEASURES

### Description of first aid measures

<b>General</b>	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly Clean contaminated shoes.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Eyes</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
<b>Skin</b>	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, immediately contact Poison Control Center. DO NOT induce vomiting unless instructed to do so by Medical personnel. Never give anything by mouth to an unconscious person.

### Important symptoms and effects, acute and delayed

<b>Overview</b>	Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and Nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or Fatal. Avoid contact with eyes, skin and clothing.
<b>Inhalation</b>	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing Dizziness, headache or nausea.
<b>Eyes</b>	Causes severe eye irritation. Avoid contact with eyes.
<b>Skin</b>	Causes skin irritation. May be harmful if absorbed through skin.
<b>Ingestion</b>	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea or drowsiness.
<b>Chronic effects</b>	No Data

# SAFETY DATA SHEET (SDS)

SDS Date: 07/31/2015 Rev. 4 Date: 5/14/2020

## SECTION 5: FIRE-FIGHTING MEASURES

<b>Conditions of flammability</b>	Material may burn but does not ignite readily. Fire may produce irritating and or toxic gasses. Heated containers may explode.
<b>Extinguishing media</b>	Use dry chemical powder, CO2 or foam, water spray may be used for large fires.
<b>Special protective equip.</b>	Wear a self-contained breathing apparatus MSHA/NIOSH (approved or equivalent), and full Protective gear.
<b>Hazardous combustion products</b>	Carbon oxides
<b>Special information</b>	Use water spray to disperse vapors and to protect personnel attempting to stop leak. Can react vigorously with oxidizing materials. Do not allow fire water contaminated with this product to enter any waterway or storm drain.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

<b>Personal precautions</b>	Wear adequate/appropriate personal protection equipment. Ventilate area if confined space.
<b>Environmental precautions</b>	Prevent further leakage or spillage if safe to do so. Do not let product enter drains or soil. Discharge into the environment must be avoided.
<b>Methods of containment/cleanup</b>	Contain liquid with dirt, sand, vermiculite or other noncombustible solids. Transfer to a metal container for disposal.

## SECTION 7: HANDLING AND STORAGE

<b>Handling</b>	Wear adequate personal protective equipment. Keep containers tightly closed. Avoid contact with skin or eyes.
<b>Storage</b>	Store in a cool, dry, well-ventilated area, protect from freezing.
<b>Incompatibilities</b>	Oxidizing agents, including nitric acid and peroxides.
<b>Suitable Packing Materials</b>	Polyethylene, poly propylene or Stainless steel (tanks/containers) Do <b>NOT</b> store in lead, steel or aluminum containers.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS No.	Ingredient	Source	Value
Proprietary	Acrylic Copolymer Emulsion	Supplier	No Controls
CAS# 107-21-1	Ethylene Glycol	ACGIH	100mg/m3 (CEILING) aerosol only
1314-13-2	Zinc Oxide	OSHA	PEL 5mg/m3 (fume) 15mg/m3 (total dust) and 5mg/m3 (respirable dust). 8hr. TWA
		ACGIH	2mg/m3 (8hr. TWA) and 10mg/m3 (STEL) for the respirable fraction
		NIOSH	5mg/m3 (fume and dust) averaged over a 10 hr. work shift, 10mg/m3 as a short term exposure limit (for fume) and 15mg/m3 (for dust), not to be exceeded at any time.
13463-67-7	Titanium Dioxide	OSHA	PEL long term value 15mg/m3 (total dust 8 hr TWA)
		ACGIH	TLV long term value 10 mg/m3 TWA (inhalable fraction 1mf/m3 TWA)
1333-86-4	Carbon Black	OSHA	3.5mg/m3 TWA
		ACGIH	3 mg/m3 TWA (inhalable fraction)

# SAFETY DATA SHEET (SDS)

SDS Date: 07/31/2015 Rev. 4 Date: 5/14/2020

1317-65-3	Calcium Carbonate	NIOSH	10mg/m <sup>3</sup> total dust; 5mg/m <sup>3</sup> respirable dust (TWA)
		OSHA	15mg/m <sup>3</sup> total dust; 5mg/m <sup>3</sup> respirable fraction (TWA)
14808-60-7	Quartz (fine fraction)	ACGIH	0.025 mg/m <sup>3</sup> Respirable Fraction
		OSHA	PEL (TWA) 0.1 mg/m <sup>3</sup>
111-76-2	2-butoxyethanol	ACGIH	20 ppm (TWA)
		OSHA	50 ppm / 240mg/m <sup>3</sup> (table Z-1 Limits for air pollutants)

PEL = Permissible Exposure Limits  
TLV = Threshold Limit Value  
EL = Excursion Limit

TWA = Time Weighted Average (8 hr.)  
STEL = Short Term Exposure Limit (15 min.)  
WEEL = Workplace Environmental Exposure Level

## Exposure Controls:

### Respiratory

Select equipment to provide protection from the ingredients listed in section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor or mist levels above the applicable limits, wear appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

### Eyes

Avoid contact with eyes. Protective equipment should be selected to provide protection from the ingredients listed in section 3 of this document. Depending on site and application method specific conditions, safety glasses, chemical goggles, and or head and face protection may be required. All equipment must be thoroughly cleaned or discarded after use.

### Skin

Select equipment to provide protection from the ingredients listed in section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. All equipment must be thoroughly cleaned or discarded after each use.

### Engineering Controls

Ensure adequate ventilation to keep exposure levels at a minimum under the specific conditions.

### Other Work Practices

Emergency eye wash stations and safety showers should be available in the immediate work area. Use good Personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove exposed/spoiled clothing and wash separately before reuse. Shower after work using plenty of soap and water.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

APPEARANCE: Gray Viscous

ODOR: Mild latex

PHYSICAL STATE: liquid

PH AS SUPPLIED: Not Measured

BOILING POINT:

F: Not Measured

C: Not Measured

MELTING POINT:

F: Not Measured

C: Not measured

FREEZING POINT:

F: Not measured

C: Not Measured

VAPOR PRESSURE (mmHg): Not Measured

@

F:

C:

VAPOR DENSITY (AIR = 1): Heavier than air

@

F:

C:

SPECIFIC GRAVITY (H2O = 1):

@ 1.200

F: 77

C:

EVAPORATION RATE: NE MIXTURE

BASIS (=1):

SOLUBILITY IN WATER: Dilutable

MIXTURE

# SAFETY DATA SHEET (SDS)

SDS Date: 07/31/2015 Rev. 4 Date: 5/14/2020

## SECTION 10: STABILITY AND REACTIVITY

Reactivity	No data available
Chemical stability	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fume generation can occur if improperly handled.
Possibility of hazardous reactions	No data available
Conditions to avoid	No data available
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Hydrogen chloride, Chlorinated compounds, Carbon Dioxide and Carbon Monoxide.

## SECTION 11: TOXICOLOGICAL INFORMATION

### TOXICOLOGICAL INFORMATION:

Breathing large amounts of hydrocarbon/ketone solvents for short periods of time adversely effects the human nervous system, the kidneys, liver, and the heart. Repeatedly breathing large amounts of toluene as when "sniffing glue" or paint can cause permanent brain damage. Human exposure studies and animal studies suggest that exposure to large amounts of solvents during pregnancy can adversely affect the developing fetus.

Ingredient	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation Vapor LC 50	Eye Damage/irritation
Acrylic Copolymer Emulsion	No Data Available	No Data Available	No Data Available	No Data Available
Ethylene Glycol	7712 (rat)	3500 (mouse)	2.5 mg/l (rat) (6 hr)	Not Classified
Zinc Oxide 1314-13-2	>5000 Rat	No sensitizing effects known	5.7 mg/l (rat) (4hr)	No sensitizing effects known
Quartz 14808-60-7	NDA Supplier	NDA Supplier	NDA Supplier	NDA Supplier
N Methyl Pyrrolidone 8752-50-4	4150 (rat)	5000 mg/kg (rat)	5.1 mg/l (rat) (4hr)	Causes serious eye irritation
2-butoxyethanol 111-76-2	1300 (rat) 1400 (guinea pig)	2000 (rat) 2000 (guinea pig)	152 mg/m <sup>3</sup> (rat)	Rabbit 24 hr. moderate
Carbon Black	8000 (rat)	3000 (rabbit)	No Data Available	No Data Available

All ingredient values, literature values

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation.
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	Not Classified	Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

# SAFETY DATA SHEET (SDS)

SDS Date: 07/31/2015 Rev. 4 Date: 5/14/2020

## SECTION 12: ECOLOGICAL INFORMATION

Ingredient	Toxicity to fish LC50	Toxicity to invertebrates LC50	Toxicity to algae EC50	Biodegradation	Bioaccumulation	Mobility in soil
Acrylic Copolymer Emulsion	No Data Available	No Data Available	No Data Available	No Data Available	No Data Available	No Data Available
Ethylene Glycol	Low acute toxicity to fish	Low acute toxicity to aquatic invertebrates	Low acute toxicity to algae	Rapidly degradable	Not expected to bioaccumulate.	Low potential for soil adsorption
Zinc Oxide	No Data Available	No Data Available	IC50 (72h)0.21 mg/l	No Data Available	Not expected to bioaccumulate	No Data Available
Calcium Carbonate	No Data Available	No Data Available	No Data Available	No Data Available	No Data Available	No Data Available
N Methyl Pyrrolidone	Not Classified	Low Acute Toxicity	Low Toxicity	Readily	Not Expected to Bioaccumulate	Low Potential for Soil Adsorption
2-butoxyethanol	1474 mg/l (Oncorhynchus mykiss) 96 hr	1550 mg/l (Water flea) 48 hr	1840 mg/l (Pseudokirchneriella Subcapitata) 72 hr	90.4% Readily biodegradable (28 day)	Low Potential	Expected to partition to water

All ingredient Values, literature values

Persistence and degradability No data available  
Bio accumulative potential Not Measured  
Mobility in soil No data available  
Results of PBT and vPvB assessment This product contains no PBT/vPvB chemicals.  
Other adverse effects No data available

## SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Waste must be disposed of in accordance with federal, state and local environmental control regulations. This product contains components that are RCRA hazardous waste. Do not flush material to drain or storm sewer. Contract to authorized disposal service. Empty containers must be handled with care due to product residue.

## SECTION 14: TRANSPORT INFORMATION

**Proper shipping name:** Water base Paint Class 55

**The product is classified:** Not classified

### Sea (IMDG):

**Class:**  
**PG:**  
**MP:** NA  
**EmS:**

**MFAG:**

**Inland Waterways:** To be handled locally.

### Air (ICAO/IATA):

**Class:**  
**PG:** NA

### Land (DOT):

**Class:** 55  
**PG:** NA  
**Primary risk label:** NA

# SAFETY DATA SHEET (SDS)

SDS Date: 07/31/2015 Rev. 4 Date: 5/14/2020

---

## SECTION 15: REGULATORY INFORMATION

---

Regulatory Overview      The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification      Not Regulated

DOT Marine Pollutants (10%):  
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):  
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):  
Ethylene Glycol

EPCRA 302 Extremely Hazardous (>.1%):  
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):  
Ethylene Glycol  
N-Methyl Pyrrolidone (>1.0%)  
2-butoxyethanol

Mass RTK Substances (>1%):  
Titanium dioxide  
Zinc oxide  
Ethylene Glycol  
Calcium Carbonate  
Quartz (fine fraction)  
N-Methyl Pyrrolidone  
2-butoxyethanol  
Carbon Black

Penn RTK Substances (>1%):  
1,2-Propylene glycol  
Titanium dioxide  
Zinc oxide  
Ethylene Glycol  
Quartz (fine fraction)

Penn RTK Substances (>1%):  
N-Methyl Pyrrolidone  
2-butoxyethanol  
Carbon Black

Penn Special Hazardous Substances (>.01%):  
(No Product Ingredients Listed)

RCRA Status:  
(No Product Ingredients Listed)

N.J. RTK Substances (>1%):  
1,2-Propylene glycol  
Titanium dioxide  
Zinc oxide  
Ethylene Glycol  
Calcium Carbonate  
Quartz (fine fraction)  
N-Methyl Pyrrolidone  
2-butoxyethanol  
Carbon Black

N.J. Special Hazardous Substances (>.01%):  
(No Product Ingredients Listed)

N.J. Env. Hazardous Substances (>.1%):  
Carbon Black



# SAFETY DATA SHEET (SDS)

SDS Date: 07/31/2015 Rev. 4 Date: 5/14/2020



**“WARNING:”** This product can expose you to chemical(s) which is/are known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).”

64-17-5	Ethanol
14808-60-7	Quartz- fine fraction
13463-67-7	Titanium Dioxide
1333-86-4	Carbon Black



**“WARNING:”** This product can expose you to chemical(s) which is/are known to the State of California to cause reproductive and developmental toxicity. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).”

64-17-5	Ethanol
14808-60-7	Quartz- fine fraction
872-50-4	2-methyl pyrrolidone

## SECTION 16: OTHER INFORMATION

### HMIS:

Health	1
Fire	1
Physical Hazard	0

### ABBREVIATIONS:

ACGIH = American Conference of Governmental Industrial Hygienists  
OSHA = Occupational Safety and Health Administration  
TLV = Threshold Limit Value  
TWA = Time Weighted Average  
PEL = Permissible Exposure Limit  
STEL = Short Term Exposure Limit  
NA = Not Applicable  
NE = Not Established  
NDA = No Data Available

V.O.C. (volatile Organic Compounds)

**83 gr/ltr**

**0.69 lb/gal**

PREPARATION INFORMATION: HMIS Hazard Ratings Scale 0 = Minimal, 1 = Slight, 2 = Moderate, 3 = Serious, 4 = Extreme

Check with supervisor for appropriate personal protection in accordance with rating.

Revised	9/1/2015	Sections 3, 8 and 11
	9/24/2015	Sections 11 and 12
	10/3/2018	Section 15
	5/14/2020	Section 9

### DISCLAIMER:

The information contained herein is based on data provided by our suppliers and relates only to the specific material identified. Flexabar Corporation believes that the information is accurate and reliable as of the preparation date of this material safety data sheet and reflects our best judgement, but no representation, guarantee or warranty expressed or implied is made as to the accuracy, reliability or completeness of the information. Flexabar Corporation urges persons receiving this information to make their own determination as to the information's suitability and completeness for their particular application.

End of Document