

FLEXDEL [Aquaculture]

Made in U.S.A.

FLEXGARD II

WATERBASE WIRE TRAP/CRAB POT ANTIFOULING PAINT

Flexgard II Waterbase Wire Trap/Crab Pot Antifouling Paint is a polyvinyl/acrylic copolymer, cuprous oxide pigmented coating formulated especially to prevent barnacles, algae, slime and other fouling organisms on wood, galvanized wire and vinyl coated wire crab, lobster and bass pots immersed in salt, brackish and fresh water. Non-toxic fumes, soap and water cleanup. Controlled leach out. Paint can be applied over existing paints that are clean, free of any debris and dry. U.S. EPA approved. Plastic container increases shelf life.

Maintaining your wire trap/crab pot's painted surfaces and periodically repainting the wire trap/crab pots is important. Marine paints and finishes help protect your wire trap/crab pots from the harsh affects of the sun, the corrosive effects of salt water, and algae and barnacle growth. Here are some step by step instructions to help you get the best results when painting wire trap/crab pots.



Application Guideline:

1. For use in salt water on wood, galvanized wire and vinyl coated wire crab; lobster and bass pots. It retards the growth of toredo worms, barnacles, algae and the hydroid stage of the hydrozoa (commonly called "hair").
2. Stir contents of container before each use.
3. The surface should be cleaned and dry before each application.
4. Apply liberally by brush or dipping. Thoroughly cover cut ends and joints.
5. If applied by brush, use two (2) coats.
6. If applied by dipping, allow article to remain in solution for three (3) minutes.
7. Allow six to eight (6-8) hours drying time between coats. Longer drying time will not cause any adverse effect on the performance of the product.
8. Allow overnight drying before use.
9. Clean tools, protective gloves and clothing with water when finished.

FLEXGARD II

WATERBASE WIRE TRAP/CRAB POT ANTIFOULING PAINT

10. Do not apply at or below freezing temperatures.
11. Repeat application on traps and lobster pots as needed.

Coverage:

Estimated coverage for diluted product is approximately 275 square feet, per gallon, depending on application.

Dilution:

Dilute up to 10% with water as needed.

Available Sizes:

In 50 U.S. Gallon Drums and 5 U.S. Gallon Pails.

Colors:

Black or Red

Cautions:

May be fatal if swallowed. May be absorbed through the skin. Causes skin irritation. Do not get in eyes, on skin or clothing. Do not breathe vapor or spray mist. Wear protective clothing and rubber gloves when handling this product. Do not allow product to freeze.

KEEP OUT OF THE REACH OF CHILDREN